

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Product Name: Cryogel® 5201, 10201

Synonyms: Silica gel, trimethylsilylated; silica aerogel materials

Use of the Substance/Preparation: High performance insulation material

Manufacturer: Aspen Aerogels, Inc.
Address: 30 Forbes Road
 Northborough, MA 01532

Telephone: (508) 691-1111

Emergency Telephone Number: 800-535-5053 US (INFOTRAC)
 352-323-3500 INTERNATIONAL

2. HAZARDS IDENTIFICATION

Appearance and Odor: White fabric material with no characteristic odor. Under certain conditions, product may have faint ammonia-like odor.

Emergency Overview: Inhalation of excessive amounts of dust from the product may cause mechanical irritation to the respiratory tract. Dermal contact may cause mechanical irritation.

POTENTIAL HEALTH EFFECTS

Inhalation: Inhalation of airborne dusts may cause mechanical irritation of the upper respiratory tract.

Eye Contact: Exposure to dust from this product can produce a drying sensation and mechanical irritation of the eyes.

Skin Contact: Skin contact with dust from this product can produce a drying sensation and mechanical irritation of the skin and mucous membranes.

Ingestion: This material is not intended to be ingested (eaten). If ingested in large quantity, the material may produce mechanical irritation and blockage

Acute Health Hazards: Dust from this product is a physical irritant, and may cause temporary irritation or scratchiness of the throat and / or itching and redness of the eyes and skin.

Chronic Health Hazards: Some studies of long term amorphous silica dust exposures indicate a potential for decreased lung function. In surveyed studies, this effect is characterized as compounded by smoking. Additionally, surveyed studies characterize the decreased lung function effect as reversible on discontinuation of exposure.

Per the fiberglass manufacturer, the fiberglass is considered textile grade and is not classified as a human carcinogenic by IARC (Group 3), ACGIH (Group A4), NTP, or OSHA.

Medical Conditions Aggravated by Exposure: Excessive inhalation of dust may aggravate pre-existing chronic lung conditions including, but not limited to, bronchitis, emphysema, and asthma. Dermal contact may aggravate existing dermatitis.

CARCINOGENICITY

Component	ACGIH	NTP	IARC
Continuous Filament Glass Fibers	A4	Not Listed	3
Amorphous Silica	NA	Not Listed	None

SECTION 2 NOTES: This product is composed of synthetic amorphous silica dioxide, often referred to as silica gel or amorphous precipitated silica. Amorphous silica should not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects from exposure to amorphous silica.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	Percent	EINECS Number	EU Classification
Silica gel, trimethylsilylated	126877-03-0	30-50	Not Assigned	None
Polyethylene terephthalate (PET or polyester)	25038-59-9	25-35	Not Assigned	None
Fibrous glass (textile grade)	NA	25-35	Not Assigned	None

4. FIRST AID MEASURES

- Eye Contact:** Immediately wash with large amounts of water for at least 15 minutes, occasionally lifting lids. If irritation occurs and persists, get medical treatment.
- Skin Contact:** Wash skin thoroughly with soap and plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Obtain medical attention if symptoms occur.
- Ingestion:** Material will pass through the body normally.
- Inhalation:** Remove to fresh air. Drink water to clear throat and blow nose to remove dust. Obtain medical attention if ill effects persist.

5. FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY PROPERTIES

Auto ignition Temperature	Not Applicable
Flash Point	Not Applicable
Flammability Limits: (Lower Explosive Limit)	Not Applicable
Flammability Limits: (Upper Explosive Limit)	Not Applicable

5.2 EXTINGUISHING MEDIA:

Use media suitable for surrounding fire and that are appropriate to the surrounding environment; normal fog nozzle water application and/or exclusion of air is typically suitable for extinguishing this product in blanket form.

5.3 PROTECTION FOR FIRE FIGHTERS

- Special Fire Fighting Procedures:** Wear NIOSH/MSHA Approved SCBA and full protective equipment.
- Unusual Fire and Explosion Hazards:** Product is a super-insulation material. Rolls of material can retain heat within internal layers causing re-ignition in the presence of oxygen if heat is not removed.
- Hazardous Decomposition Products:** Primary combustion products are carbon monoxide and carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

- Personal Precautions:** Minimize dust generation. Ensure adequate ventilation. Use personal protective equipment as necessary.
- Environmental Precautions:** Material is not soluble. Do not flush into surface water or sanitary sewer system.
- Methods for Cleaning Up:** Contain and collect released material for proper disposal. A HEPA-filter equipped vacuum is the preferred method of cleaning up.

7. HANDLING AND STORAGE

Handling Aerogel blankets will generate dust when handled. Workplace exposure to all dusts should be controlled with standard industrial hygiene practices. Local exhaust ventilation should be the primary dust control method. Dust released during the handling of aerogel blankets should be cleaned up promptly. Dry vacuuming using a HEPA (High Efficiency Particulate Air) filter is the preferred method for cleaning up dust. Sweeping is not an effective method of picking up aerogel dust. Because aerogel dust is hydrophobic, water is not effective as a dust control agent.

Storage Aerogel blankets should be kept in their packaging until they are ready to be used. Unpack the material in the work area. This will help to minimize the area where dust exposure may occur. Trimmed material and scrap should be promptly packed in disposal bags.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Limit Values

There are no exposure limits identified for the main product component, classified as synthetic amorphous silica. Exposure limits for synthetic amorphous silica are based on silica (CAS No. 7631-86-9).

CAS Number	Component Name	Exposure Limits
7631-86-9	Silica, Amorphous	Germany TRGS 900
		UK WEL
		US OSHA PEL (TWA) ^a :
		US ACGIH ^b
NA	Continuous filament glass fibers	US ACGIH
		US OSHA

4 mg/m³ (inhalable fraction)
6 mg/m³ (total inhalable fraction)
2.4 mg/m³ (respirable fraction)
15 mg/m³ (total dust)
5 mg/m³ (respirable fraction)
10 mg/m³ (inhalable)
3 mg/m³ (respirable)
1.0 fibers/cc^c
5 mg/m³ (inhalable)
10 mg/m³ (total dust)
5 mg/m³ (respirable fraction)

^a The US OSHA standard for amorphous silica is: (80 mg/m³)/(%SiO₂). The NIOSH Sampling Method 7501 for Amorphous Silica calculates the %SiO₂ based on the percentage of crystalline silica in the sample. Because the percentage of crystalline silica in aerogel is 0%, the particulate limit applies.

^b US ACGIH based on Particles Not Otherwise Specified (PNOS)

^c Respirable fibers: length >5 μm; aspect ratio ≥3:1, as determined by the membrane filter method at 400–450X magnification (4-mm objective), using phase-contrast illumination. US NIOSH length μm, width <3 μm diameter and length:width ratios ≥3.

8.2 Exposure Control

- Ventilation:** Local exhaust in accordance with general industrial hygiene practices is recommended to control dust.
- Respiratory Protection:** If conditions are present involving dust evolution above the occupational exposure limit, wear properly fitted NIOSH/MSHA approved respirator with P100 cartridge or canister. A respiratory protection program that meets applicable local regulations should be implemented whenever workplace conditions warrant use of a respirator.
- Hand Protection** Silica aerogels are hydrophobic (repel water) and may cause drying and irritation of the skin, eyes, and mucous membranes. For this reason, nitrile, latex, or other impermeable gloves should be worn when handling aerogel blankets.
- Eye Protection:** Safety glasses, or chemical goggles as needed to provide greater protection from dust.

Skin Protection: Long-sleeved, long-legged work clothes are also advised. Disposable coveralls should be considered to minimize skin exposure and track out of aerogel dusts into adjacent areas.

Work Hygienic Practices Keep materials packaged until just prior to use. Die cut in preference to rotary or other cutting methods. Dry vacuum with proper filtration preferred to sweeping. Wash thoroughly after using the product. Wash clothing if dusty conditions present. Wash hands before eating or drinking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White fabric blanket
Odor: No characteristic odor. Under certain conditions, product may have faint ammonia-like odor.
pH: Not applicable.
Boiling Point/Range: Not applicable.
Flash Point: Not applicable.
Flammability (solid, gas): Not applicable.
Explosive Properties: Not applicable.
Oxidizing Properties: Not applicable.
Vapor Pressure: Not applicable.
Solubility: Insoluble.
Viscosity: Not applicable.
Evaporation Rate: Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable
Conditions to Avoid: Prolonged exposure to temperatures above the recommended use temperatures.
Materials to Avoid: None known
Hazardous Decomposition Products Under recommended usage conditions, hazardous decomposition products are not expected.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Dust may cause mechanical irritation and dryness to eyes and skin.

Synthetic Amorphous Silica

Oral LD50: >5,000 mg/kg
Inhalation LC50: >2,000 mg/m³
Dermal LD50: >3,000 mg/kg
Eye Irritation: Synthetic amorphous silica and silicates are not irritating to skin and eyes under experimental conditions, but may produce dryness following prolonged and repeated exposure.
Skin Irritation: Synthetic amorphous silica and silicates are not irritating to skin and eyes under experimental conditions, but may produce dryness following prolonged and repeated exposure.

CHRONIC TOXICITY

Some studies of long term amorphous silica dust exposures indicate a potential for decreased lung function. In surveyed studies, this effect is characterized as compounded by smoking. Additionally, surveyed studies characterize the decreased lung function effect as reversible on discontinuation of exposure.

CARCINOGENICITY

The International Agency for Research on Cancer (IARC) considers synthetic amorphous silica to be not classifiable as to its carcinogenicity to humans (Group 3). According to the manufacturer, the fiberglass in this product is considered textile grade fibrous glass and it is not classified as a carcinogen by ACGIH, IARC, NTP or OSHA.

NOTE TO SECTION 11: Toxicological information is based on literature review for synthetic amorphous silica (CAS No. 7631-86-9)

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Synthetic Amorphous Silica Fish: LC50 > 10,000 mg/L (Brachydanio rerio: 96 hour), Method OECD 203
Daphnia magna: EC50 > 10,000 mg/l (24 hours), Method OECD 202

Mobility None expected due to insoluble nature of product.

Persistence and Biodegradability Not applicable for inorganic material.

Bioaccumulative Potential None expected due to insoluble nature of product.

Other Adverse Effects None expected.

NOTE TO SECTION 12: Ecological information is based on literature review for synthetic amorphous silica (CAS No. 7631-86-9)

13. DISPOSAL CONSIDERATIONS

Dispose in an approved landfill in accordance with federal, state / provincial, and local regulation. Cover promptly to avoid dust generation. This product is not regulated as a hazardous waste under US RCRA regulations.

14. TRANSPORT INFORMATION

Shipping Name:	Not regulated for transport
Hazard Class	None
UN Number	None
Packing Group	None
Required Label(s)	None
Marine Pollutant	No
Additional Information	None

15. REGULATORY INFORMATION

EC REGULATORY INFORMATION

Product is not classified as a dangerous material or preparation as defined in EC Directives 67/548/EEC or 1999/45/EC.

U.S. FEDERAL REGULATIONS

CERCLA (Comprehensive Response Compensation and Liability Act): Product is not classified as hazardous or reportable under this requirement.

SARA TITLE III (Superfund Amendments and Reauthorization Act): Product is not classified as hazardous or reportable under this requirement.

311/312 HAZARD CATEGORIES: Materials in this product are classified as hazardous or reportable under this requirement.

313 REPORTABLE INGREDIENTS: Materials in this product are classified as hazardous or reportable under this requirement.

STATE REGULATIONS: Materials in this product appear on the following state hazardous substance lists: CA, IN, KY, MA, MN, NC, NJ, OR, PA. Check individual state requirements

INTERNATIONAL REGULATIONS Amorphous silica (CAS No. 7631-86-9), are listed on the WHMIS Ingredient Disclosure List at a concentration threshold of 1 %.

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances.

16. OTHER INFORMATION

NFPA HAZARD CLASSIFICATION

Health **1**
Flammability **1**
Reactivity **0**
Other **N/A**

HMIS HAZARD CLASSIFICATION

Health **1**
Flammability **1**
Reactivity **0**
Protection **Please refer to Section 8.**

ABBREVIATIONS:

NA	Denotes no applicable information found or available.
CAS Number	Chemical Abstract Service Number
EINECS Number	European INventory of Existing Chemical Substances
ACGIH	American Conference of Governmental Industrial Hygienists
US OSHA	United States Occupational Safety and Health Administration
TLV	Threshold Limit Value
PEL	Permissible Exposure Limit
TWA	Time-weighted average
IARC	International Agency for Research on Cancer
EU	European Union
NTP	National Toxicology Program
R	Risk
S	Safety
LC50	Lethal Concentration 50%
LD50	Lethal Dose 50%
NFPA	National Fire Protection Association
HMIS	Hazardous Materials Identification System
US DOT	United States Department of Transportation
TDG	Transportation of Dangerous Goods Regulation

Section 11 Synthetic Amorphous Silica Toxicity Information Reference: United Nations Environmental Programme (UNEP), Organization for Economic Co-operation and Development (OECD) Screening Information Data Set (SIDS) Initial Assessment Report, Synthetic Amorphous Silica, July 23, 2004.

Revision Summary: This revised safety data sheet replaces all previous versions. The safety data sheet was modified to update format and clarify content.

DISCLAIMER: The information herein is presented in good faith and believed to be accurate as the effective data given. However, no warranty, expressed or implied, is given. It is the user's responsibility to ensure that its activities comply with Federal, State or Provincial, and local laws.